



PEXOL ATF D III

Product Description and Field of Use

Automatic installation of passenger or commercial vehicles requiring GM Dexron IIIH or earlier specifications. It is suitable for use in transmissions. Also in hydraulic power and power steering systems when recommended by the equipment manufacturer available. Provides easier and quieter gear shifts when very cold.

Properties and Benefits

- Automatic transmission with high quality additives that prevent rust, corrosion and oxidation. Protects perfectly.
- It minimizes friction in wide operating temperature ranges, dissipates heat, and reduces gear changes. Provides ease.
- It exceeds the expectations of engine manufacturers at the maximum level with its electronic control and superior power transmission features meets.
- It has high cutting resistance.

Specifications and Approvals Fulfilled

Dexron IID/IIIE/IIIF/IIIG/IIIH, MB 236.1/236.5/236.6/236.7/236.9, Ford Mercon/M2C138-CJ/166-H, MAN 339 Typ Z1/V1, Allison C4/TES-389, Cat TO-2, Voith 55.6335 (G607), Volvo 97341, BMW 81 22 9 407 738, ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A, 14B, GM TYPE A SUFFIX A (TASA)

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.862
K. Viscosity, @ 100°C	cSt	ASTM D 445	7,6
Viscosity Index		ASTM D 2270	170
Flashing Point	°C	ASTM D 92	219
Pour Point	°C	ASTM D 97	-45

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.