



PEXOL P3 10W-40

Product Description and Field of Use

A universal motor oil, recommended for use in petrol-and diesel engines, with or without turbocharging, in passenger cars and delivery vans.

Properties and Benefits

- Maintains performance thanks to superior thermal and oxidation stability during the longest oil change period recommended by vehicle manufacturers.
- Outperforms in variable weather conditions thanks to its high viscosity index.
- Reduces oil consumption thanks to its low volatility and thus helps to reduce hydrocarbon pollution.

Specifications and Approvals Fulfilled

ACEA A3/B4, API SL/CF, BMW Longlife-98, MB 229.1, VW 501.01/505.00

Typical Properties*

| TEST | UNIT | TEST METHOD | TYPICAL VALUES |
|-----------------------|-------------------|-------------|----------------|
| Density, @15 °C | g/cm ³ | ASTM 4052 | 0.864 |
| K. Viscosity, @ 100°C | cSt | ASTM D 445 | 13,5 |
| Viscosity Index | | ASTM D 2270 | 153 |
| CCS-25°C | mPa s | ASTM D 5293 | Max.7000 |
| Flashing Point | °C | ASTM D 92 | 216 |
| Pour Point | °C | ASTM D 97 | -39 |

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.