TECHNICAL DATA SHEET

PEXOL P7 5W-30 GF-6

Product Description and Field of Use

Product is new requiring dexos 1 Gen 2 specification generation General Motors gasoline passenger vehicle early ignition (LSPI) at low speeds in engines. It was specially developed to prevent.

Properties and Benefits

- Prevents premature ignition (LSPI) at low speeds.
- Has the highest API classification, also with previous API classifications is compatible.
- Provides high durability and fuel economy. With new additive technology, only does not protect the environment and keeps the turbocharger and intercooler clean.
- Thanks to rapid oil circulation, it reduces wear and tear, especially during engine warm-up. Minimizes oil change intervals and ensures long oil change intervals.

Specifications and Approvals Fulfilled

API SP Resource Conserving, ILSAC GF-6A, GM dexos1™ Gen 2, Chrysler MS 6395, Ford WSS-M2C946-A/B1/WSS-M2C961-A1

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm^3	ASTM 4052	0.850
K. Viscosity, @ 100°C	cSt	ASTM D 445	11,3
Viscosity Index		ASTM D 2270	175
CCS-30°C	mPa s	ASTM D 5293	Max.6600
Flashing Point	°C	ASTM D 92	224
Pour Point	°C	ASTM D 97	-33

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.